

DECLARATION OF PERFORMANCE

*In compliance with EU Regulation (EU): No 305/2011
(Construction Product Regulation)*

Declaration of Performance-Nr. **BS 00260**

1. Unique identification code of the product-type:

BIS PU FLEX BK CQ 300ML*12 ENRO

2. Intended use(s):

Sealants for facade elements for interior and exterior applications,

3. Manufacturer:

Bison International BV, Dr. A.F. Philipsstraat 9, 4462 EW Goes, The Netherlands

4. Authorized representative:

Not Applicable

5. System or systems of assessment and verification of constancy of performance:

System 3

System 3 for reaction to fire according class E

6. Harmonised standard: **EN 15651-1: 2012; F-EXT-INT-CC (25 LM)**
Notified body/ies: **FUNDACION TECHNALIA RESEARCH & INNOVATION (1292)**

7. Declared performance

Conditioning:	Method A	(according to ISO8340)
Substrate:	Glass	(no use of primer)
	Mortar M2	(no use of primer)

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1 :2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and Air tightness		
Resistance to flow	≤3 mm	
Loss of Volume	≤ 10%	
Tensile properties (i.e. elongation): at maintained extension after water immersion(23°C)	Pass	
Cold Climate Areas (-30°C)		
Tensile properties (i.e. secant modulus):	≤0,9 Mpa	
Tensile properties (i.e. at maintained extension) :	Pass	
Durability	Pass	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not Applicable**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

J.P.M. Klerks
 Manager Reseach & Development
 Goes, 3. November 2016

